

ILLUCENT LINEAR

4', 6', 8'

Sustainably Constructed
 100% Recycled Aluminum
 Recyclable Acrylic
 Single Channel Distribution
 25% Indirect/75% Direct
 UL 924, UL 1598, UL 2108
 Advanced Dimming 0-10V, Down to 1%
 DALI Tunable White
 Human-Centric Options
 L90>71,000
 10-Year Warranty

UL Certified for Elevated Ambient
 Operating Temperatures
 70°C Remote
 55°C Integral
 35°C Emergency Battery

Remote Distributed Low Voltage
 Integral Class 2 Driver 120-277V
 Integral with Onboard Emergency
 Power over Ethernet (PoE)



Size	Top	Bottom	Height	Weight
4'	47"	48.2	2.6"	4 lbs
6'	70.2"	71.5"	2.6"	6 lbs
8'	93"	94.2"	2.6"	8 lbs



Size	Top	Bottom	Height	Weight
4'	46.2"	48.2"	4"	6 lbs
6'	69.5"	71.5"	4"	10 lbs
8'	92.2"	94.2"	4"	12 lbs

Declare. TAA



Available Colors



LUMEN PACKAGES (Delivered lumens tested at 4000K 80 CRI Remote/Integral, 5000k 97 CRI Circadian/Tunable)

Size	SKU	Total Watts	Integral		Remote/PoE		Circadian	Tunable
			162 Lm/W 80 CRI	135 Lm/W 90 CRI	165 Lm/W 80 CRI	137 Lm/W 90 CRI	119 Lm/W 97 CRI	91 Lm/W 97 CRI
4'	L1	20	3241	2690	3294	2734	2372	1826
	L2	30	4861	4035	4941	4101	3558	2739
	L3	40	6482	5380	6588	5468	4744	3652
6'	L1	30	4861	4035	4941	4101	3558	2739
	L2	45	7292	6052	7412	6152	5337	4109
	L3	60	9722	8070	9882	8202	7116	5478
8'	L1	40	6482	5380	6588	5468	4744	3652
	L2	60	9722	8070	9882	8202	7116	5478
	L3	80	12963	10759	13176	10936	9488	7304

ORDERING INFORMATION

FIXTURE	POWER	SIZE	MOUNT	LUMENS	COLOR	CRI	INTEGRAL WHIP	
ILIN-Illucent Linear	I-Integral	4-4 Foot	P-Pendant	L1-	30-3000K	80-80+ CRI	3-No Dim	
	IEM-Emergency	6-6 Foot	S-Surface	L2-	35-3500K	90-90+ CRI	5-Dim	
	R-Remote	8-8 Foot	U-Unistrut	L3-	40-4000K	97-Circadian	3E-No Dim EM On	
	POE-PoE					50-5000K		4E-No Dim EM On/Off
						65-6500K		5E-Dim EM On
						DC-Dynamic Circadian		6E-Dim EM On/Off
						TW-Tunable White (Integral)		
WHIP COLOR*	FEED*	FINISH		ENDCAP		SENSOR**		
W-White	TF-Top Feed	CW-Clear Anodized Aluminum		WP-White Plastic		ES-Keilton LV - Remote/Integral		
B-Black	SF-Side Feed	BB-Black Anodized Aluminum		BP-Black Plastic		SE-Smartengine PoE - Remote		
S-Silver Braided		CC-Custom Color (certain restrictions apply)		CM-Metal Clear Anodized		LU-Lutron - Integral		
						EN-Enlighted - Integral		
						LM-Lantana Microwave - Integral		
						MC-McWong/Casambi - Integral		

Specifications subject to change without notice.
 Revision Date: 03/07/2024

LANTANA LED

WWW.LANTANALED.COM